

کلید گردان دوفاز یک طرفه ۲۵ آمپر KA2502



مشکی

رنگ بدنه

پلاستیک، فلز

جنس بدنه

25

جریان (آمپر)

2

تعداد فاز

ندارد

درپوش

IP65

درجه حفاظت

24 ماهه الکترو کاوه

گارانتی



کلید گردان دوفاز یک طرفه ۱۶ آمپر KA1602



ابعاد نصب

Plastic Plate Version						Installation Diagram						Pad Lock Plate Version						
Series	A	A1	A2	B	B1	R	C	P	S	Q	L1	L2	L3	D1	D2	S1	S2	S3
A16.00	52	19	7	52	24	10	22	12	16	39	—	37	28	4	4	2.9x9.5	3.5x10	2.9x6.5
	64	20	9	75	28	10	24	12	16	39	—	47	28	4	4	2.9x9.5	3.5x10	2.9x6.5
	75	20	9	75	28	10	24	18	20	58	44	59	28	4	4	2.9x9.5	3.5x10	2.9x6.5
A25.00	64	20	9	75	28	10	24	18	20	58	44	59	28	4	4	2.9x9.5	3.5x10	2.9x6.5
	75	20	9	75	28	10	24	18	20	58	44	59	28	4	4	2.9x9.5	3.5x10	2.9x6.5
	105	30	11	105	40	10	24	18	20	58	—	85	28	5.5	5.5	4x10	3.5x12	2.9x11
A50.00	105	30	11	105	40	12	36	18.3	20	73	—	85	40	5.5	5.5	4x10	5x12	2.9x11
A63.00	105	30	11	105	40	12	36	25	30	84	—	85	40	5.5	5.5	4x10	5x12	2.9x11
A100.00	130	42	13	—	—	16.5	46	30	30	110	—	110	89	5.5	5.5	5x20	5x25	2.9x13
A200.00	130	42	13	—	—	16.5	46	39	30	110	—	110	89	5.5	5.5	5x20	5x25	2.9x13

Chase Assembly Of Plastic Or Pad -Lock Plate

Series	A	B	C	D	E	F
A16.00	52	36	36	40	4	36
	64	48	48	40	4	48
	75	44	44	40	4	58
A25.00	64	48	48	58	4	58
	75	44	44	58	5.5	85
	105	85	85	58	5.5	85
A50.00	105	85	85	73	5.5	85
A63.00	105	85	85	84	5.5	85
A100.00	130	95	95	110	5.5	110
A200.00	130	95	95	110	5.5	110

Metal Back Plate Assembly

Series	L1	L2	L3	L4	D1	D2	D3	Q	P
A16.00	18	27	60	28	4	5	4	71	10
A25.00	18	27	60	28	4	5	4	71	10
A50.00	26	40	87	40	5.3	5.3	5.3	99	12.5
A63.00	26	40	87	40	5.3	5.3	5.3	99	12.5

Assembly Template

Series	L1	L2	L3	L4	D1	D2	D3
A100.00	89.5	96	40	30	5.5	15	10
A200.00	89.5	96	40	40	5.5	15	10

ابعاد به میلی متر هستند.

