

کلید گردان دوفاز یک طرفه ۴۰ آمپر KA4002



رنگ بدنه

مشکی

جنس بدنه

پلاستیک، فلز

جریان (آمپر)

40

تعداد فاز

2

درپوش

ندارد

درجه حفاظت

IP65

گارانتی

24 ماهه الکترو کاوه



کلید گردان دوفاز یک طرفه ۴ آمپر KA4002



ابعاد نصب

Plastic Plate Version							Installation Diagram							Pad Lock Plate Version						
Series	A	A1	A2	B	B1	R	C	P	S	Q	L1	L2	L3	D1	D2	S1	S2	S3		
A16.00	52	19	7	52	24	10	22	12	16	39	—	37	28	4	4	2.9x9.5	3.5x10	2.9x6.5		
	64	20	9	75	28	10	24	12	16	39	—	47	28	4	4	2.9x9.5	3.5x10	2.9x6.5		
	75	20	9	75	28	10	24	18	20	58	44	59	28	4	4	2.9x9.5	3.5x10	2.9x6.5		
A25.00	64	20	9	75	28	10	24	18	20	58	44	59	28	4	4	2.9x9.5	3.5x10	2.9x6.5		
	75	20	9	75	28	10	24	18	20	58	44	59	28	4	4	2.9x9.5	3.5x10	2.9x6.5		
	105	30	11	105	40	10	24	18	20	58	—	85	28	5.5	5.5	4x10	3.5x12	2.9x11		
A50.00	105	30	11	105	40	12	36	18.3	20	73	—	85	40	5.5	5.5	4x10	5x12	2.9x11		
A63.00	105	30	11	105	40	12	36	25	30	84	—	85	40	5.5	5.5	4x10	5x12	2.9x11		
A100.00	130	42	13	—	—	16.5	46	30	30	110	—	110	89	5.5	5.5	5x20	5x25	2.9x13		
A200.00	130	42	13	—	—	16.5	46	39	30	110	—	110	89	5.5	5.5	5x20	5x25	2.9x13		

Chase Assembly Of Plastic Or Pad -Lock Plate													
Series	A	B	C	D	E	F							
A16.00	52	36	36	40	4	36							
	64	48	48	40	4	48							
	75	44	44	40	4	58							
A25.00	64	48	48	58	4	58							
	75	44	44	58	5.5	85							
	105	85	85	58	5.5	85							
A50.00	105	85	85	73	5.5	85							
A63.00	105	85	85	84	5.5	85							
A100.00	130	95	95	110	5.5	110							
A200.00	130	95	95	110	5.5	110							

Metal Back Plate Assembly													
Series	L1	L2	L3	L4	D1	D2	D3	Q	P				
A16.00	18	27	60	28	4	5	4	71	10				
A25.00	18	27	60	28	4	5	4	71	10				
A50.00	26	40	87	40	5.3	5.3	5.3	99	12.5				
A63.00	26	40	87	40	5.3	5.3	5.3	99	12.5				

Assembly Template													
Series	L1	L2	L3	L4	D1	D2	D3						
A100.00	89.5	96	40	30	5.5	15	10						
A200.00	89.5	96	40	40	5.5	15	10						

ابعاد به میلی متر هستند.

