

Surface mounting	No
Flush-mounted installation	Yes
Duct installation	Yes
Floor box/subfloor mounted	Yes
Type of fastening	Engage (snap)
Assembly arrangement	Basic element with central cover plate
Type of connector	RJ45 8(8)
With buses/couplings	Yes
Suitable for number of connectors	1
Category	6
Colour	White
RAL-number	9003
Connection type	Insulation displacement connector
Shielded buses	No
Separate earthing connection	No
With label space	Yes
Separate strain relief	No
Mounting method shielding connection	None
Outlet direction	Straight
With dust cover	Yes

Degree of protection (IP)	IP20
Colour coding	Yes
Device width	45 mm
Device height	45 mm
Device depth	33.7 mm
Number of modules (module system)	2
Built-in depth	25.2 mm
Degree of impact strength (IK)	IK03
Operating / setting temperature	-40-70 °C
Storage temperature	-40-70 °C
Terminal marking indication	Yes
Halogen free	Yes
Antimicrobial treatment	No
Mounting method	Flush-mounted
Tube diameter for wall mounted product	0-0 mm
Maximum Input cable diameter	9 mm
Entry membrane gland type	Not applicable
Vertical fixing center distance	0-0 mm
Horizontal fixing center distance	0-0 mm
Cable support	Not applicable